



Product Data Sheet

Trinity NGEO Performance Plus 40w Low Ash Stationary Natural Gas Engine Oil

- **Trinity NGEO Performance “Plus”** is formulated for long life and extended drain intervals used in high BMEP stationary gas engines.
- **Trinity NGEO Performance “Plus”**
 - Hyper-ZDDP chemistry delivers measurable wear protection and guards against equipment failure while lowering the overall cost of ownership.
 - Protects against deposits and sludge formation
 - Formulation is tailored to the higher temperatures and outputs of more modern stationary natural gas engines.
- **Trinity NGEO Performance “Plus”** antioxidant performance improves oil life and enables extended drain intervals of (2000 - 4000+ hrs).
- **Trinity NGEO Performance “Plus”** is a “Proven Performance” product, passing OEM field trials operating in:
 - Caterpillar G3612 field test report # PAP 531 2012 SG
 - Waukesha F3521 field test report # PAP 375 2014 SG

360 Compression Services

offers:

“State of the Art”

Oil Condition Monitoring Program delivered
by an independent Third-Party Lab.

- Free Monthly Testing
- Prepaid Sample Shipping
- Sample Management Training
- Cloud Base Reporting
- Trend Analysis
- Archived Reports and Trend History
- Asset Performance Comparison

Trinity NGEO Performance Plus	40w Low Ash
Viscosity @100C	13.9
Viscosity @40C	130.5
Flash Pt	254C / 490F
Specific Gravity	.884
Viscosity Index	103
TBN mg/g KOH	6
Pour Point °C/°F	-27 / -18

This product meets or exceeds the OEM specifications for:

- Caterpillar
- Waukesha
- Jenbacher
- MWM
- Cummins
- Man Diesel & Turbo 4T
- Guascor
- MTU
- Dresser Rand
- Niigata
- Wartsila 4T

832-499-2821

info@360compserv.com

27663 Concho Dr, Splendora, TX 77372 USA

www.360compserv.com