

Product Data Sheet



FLEET PRO MONOGRADES SAE 10W, 30, 40 & 50 | Heavy Duty

Product Description

FLEET PRO MONOGRADES are high performance heavy duty motor oils recommended for older four-stroke gasoline and diesel engines¹.

FLEET PRO MONOGRADES meet the API service requirements of CF², CF-2 ²/ SL and are formulated utilizing Group II base oils and nowadays additive technology to provide outstanding protection for engines where these monograde viscosity is required by the OEM³.

Technical Data

(typical values)

SAE GRADE	ASTM	10W	30	40	50
Product Number		07-129010	07-129030	07-129040	07-129050
SDS Number		S118			
Viscosity @ 100°C, cSt	D445	5.79	12.07	14.43	18.73
Viscosity @ 40°C, cSt	D445	31.02	100.3	133.4	190.5
Viscosity Index	D2770	131	111	107	110
Specific Gravity at 60°F	D4052	0.8597	0.8788	0.8822	0.881
Pour Point, °C	D5950	-42	-33	-33	-33
Color ASTM	D1500	L3.0	L3.0	L3.0	3
CCS, cP	D5293	2,500 (-25°C)	NA	NA	NA
Flash Point COC, °C	D92	200	220	220	245
TBN	D2896	7.1	7.2	7	7.2

1. Always follow your operator's manual for recommended viscosity grade and API service classification
2. Obsolete specifications
3. Consult your owner's manual regarding its suitability for use in equipment from other OEMs

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.

