



FLEET PRO PLATINUM SYN BLEND 10W-30 FA-4 | Heavy Duty

Product Description

FLEET PRO PLATINUM SYNTHETIC BLEND 10W-30 FA-4 is specially formulated for use in select high-speed four-stroke cycle diesel engines designed to meet 2017 model year on-highway greenhouse gas (GHG) emission standards. This oil is formulated to use in on-highway applications with diesel fuel sulfur content up to 15 ppm (0.0015% by weight). It is blended to a high temperature high shear (HTHS) viscosity range of 2.9 cP - 3.2 cP to assist in reducing GHG emissions. It is especially effective at sustaining emission control system durability where particle filters and other advanced after treatment systems are used.

FLEET PRO PLATINUM SYNTHETIC BLEND 10W-30 FA-4 heavy diesel engine oil is designed to provide enhance protection against oil oxidation, viscosity loss due to shear, and oil aeration as well as protection against catalyst poisoning, particulate filter blocking, engine wear, piston deposits, degradation of low- and high-temperature properties, and soot-related viscosity increase.

Industry and OEM Specifications

- API FA-4¹
- DFS 93K223
- CES 20087

Features

- Provides optimum emission control systems protection (DPF), for minimal downtime
- Excellent low temperature properties helps speed cold starts
- Exceptional oxidation and thermal stability that combined with superb detergency minimize piston and turbocharger deposits
- Improved fuel economy²


The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



FLEET PRO PLATINUM SYN BLEND 10W-30 FA-4 | Heavy Duty

Technical Data

(typical values)



SAE GRADE	ASTM	10W-30
Product Number		07-608610
SDS Number		S118
Viscosity @ 100°C, cSt	D445	9.95
Viscosity @ 40°C, cSt	D445	65.01
Viscosity Index	D2770	137
Specific Gravity at 60°F	D4052	0.871
Pour Point, °C	D5950	-42
Color ASTM	D1500	L3.5
CCS at -25°C, cP	D5293	5,900
Flash Point COC, °C	D92	220
TBN	D2896	10.2
Sulfated Ash, %m	D874	0.96
HTHS @ 150°C, mPa s	D4683	2.96
Noack, %m	D5800	12.11

1. API FA-4 oils are NOT interchangeable or backward compatible with API CK-4, CJ-4, CI-4 Plus, CI-4 or CH-4 oils. Always follow your operator's manual for recommended viscosity grade and API service classification
2. Up to 1.3% improvement vs. SAE 15W-40 oils in Class 8 bench engine testing programs

The recommended shelf life for these oils is typically 48 months from manufacturing date when stored properly in the original sealed containers.

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.

