



MAJESTIC | Multigrade Automotive Synthetic Gear Oils (LS)

Product Description

MAJESTIC Multigrade Automotive Synthetic Gear Oils are synthetic fluids formulated with a premium limited slip additive package to provide improved extreme pressure protection under high load operation. These fluids were engineered to provide excellent fluid shear stability and superb frictional characteristics to promote smooth, easy shifting.

MAJESTIC Multigrade Automotive Synthetic Gear Oils have improved thermal stability at high temperatures resulting in less deposit formation and better compatibility with seals. The high-performance additives allow for excellent resistance to rust and corrosion and are compatible with various types of ferrous and yellow metals.

Industry and OEM specifications²

- ◆ API GL-5 and MT-1
- ◆ SAE J2360
- ◆ MAN 342 M-1, M-2
- ◆ Mack GO-J
- ◆ Scania STO 1.0
- ◆ NATO O-226
- ◆ ZF TE ML-07A & ML-08

Applications

MAJESTIC Multigrade Automotive Synthetic Gear Oils are recommended for domestic and imported heavy duty commercial vehicle rear axles and differential lubricants in over-the-road and off-road vehicles when operating under severe conditions and in extremely cold or hot environments. These lubricants provide the potential for improving fuel economy and extending drain intervals. These oils are capable of 250,000¹ miles drain intervals.

Features

- ✓ Excellent fluidity at low temperatures assures faster lubrication of components and easier shifting of transmissions.
- ✓ Prevent corrosion and rusting of transmission and differential components.
- ✓ Outstanding anti-foam protection.
- ✓ Exceptional thermal and oxidation stability.
- ✓ Excellent seal compatibility.
- ✓ Extended drain capabilities with exceptional axle wear protection under the high temperature conditions demanded by passenger car OEMs for towing and off-road application.
- ✓ Protection durability as defined by the ASTM L37 test.
- ✓ Better overall performance when compared with conventional mineral oil-based gear lubricants.



Technical Data

		75W-90	75W-140	80W-140
Product Number		07-392759	07-392751	07-392801
SDS Number		S174		
Viscosity @ 100°C, cSt	D445	16.24	26.65	28.89
Viscosity @ 40°C, cSt	D445	103.0	165.3	211.3
Viscosity Index	D2270	170	198	176
Specific Gravity at 60°F	D4052	0.8480	0.8469	0.8516
Pour Point, °C	D5950	-42	-45	-39
Color ASTM	D1500	L1.0	L0.5	L1.0
Brookfield, cP	D2983	107,000 @-40°C	106,400 @-40°C	37,850 @-26°C
Flash Point, °C	D92	200	203	205
Copper Corrosion	D130	2C		

1. Heavy Duty Class 8 trucks, follow the OEM drain interval (miles or hours) for synthetic oil up to 250,000 miles or three years, whichever comes first.
2. Meets the requirements of this standard and it is capable of being approved.
3. Always follow the operator's manual to confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and the customer's maintenance practices.

The recommended shelf life for these oils is typically 24 months from manufacturing date when stored properly in the original sealed containers.

The product described above is designed for a specific use and may not be valid for other uses not specified in our specification sheet or in applications not requiring this specific product. Pinnacle Oil believes the information presented in this specification is accurate at the time written and is based upon internally generated information and information as presented by its vendors. No representation, warranty, or guarantee is made as to its accuracy or completeness. We do not accept any liability for any loss or damage that may occur from the use of this information.



Pinnacle Oil Holdings LLC.

www.PinnacleOil.com

Toll Free: 1-800-829-8899 | Tel: 1-317-875-9465